


05308600 - LUNETTA H50 PUMA TL2000-2500

Type	STEADY REST Self-centering steady rest for turret
Mounting	SPECIAL FIXING ATTACK
Tool output	Gripping jaws Ø5-Ø60
Coolant	N.A.
H [mm]	50
Ø Min [mm]	5
Ø Max [mm]	60
Max pressure [bar]	14
Accessories	N.A.
Notes	N.A.
Mounting tips	Lower turret



Always check live tool dimensions on the turret

Dimensions: 15,9~ (top), 247 (left), 227 (left), 142 (bottom), 80 (bottom), 194,6~ (bottom), 55 (right), 100 (right), 110 (right), 20 (top), 50 (left), 197 (left), 74 (bottom), 189,5 (bottom).

Clamping diameters: Ø 60 max, Ø 5 min.

DIAGRAMMA di BLOCCAGGIO FORZA MOLLA
CLAMPING DIAMETER DIAGRAM SPRING FORCE

DIAGRAMMA FORZA TOTALE SENZA MOLLA
TOTAL FORCE DIAGRAM WITHOUT SPRING

Tipo molla D-313W
Rata molla 5,961 N/mm
Forza max 377,4 N
Forza con lunetta chiusa 342,7 N
Forza con lunetta aperta 152 N

Spring type D-313W
Spring rate 5,961 N/mm
Force max 377,4 N
Force with closed steady-rest 342,7 N
Force with open steady-rest 152 N

Tipo molla D-313G
Rata molla 6,451 N/mm
Forza max 392 N
Forza con lunetta chiusa 389 N
Forza con lunetta aperta 182,5 N

Spring type D-313G
Spring rate 6,451 N/mm
Force max 392 N
Force with closed steady-rest 389 N
Force with open steady-rest 182,5 N

Ø cilindro 60mm
Superficie pistone 28,27 cm²
Corsa max 32,5mm
Max. pressione d'esercizio 14bar
Max. forza di bloccaggio/rollio 100daN
Max. velocità pastiglia/rollio 800m/min
Precisione di centraggio (tolleranza di precisione a DIN ISO1101) su tutta la zona di bloccaggio alle stesse condizioni di bloccaggio 0,02mm
Precisione di ripetibilità con lunetta allineata sul diametro di bloccaggio 0,005mm.

Cylinder dia. 60mm
Piston surface 28,27 cm²
Max stroke 32,5mm
Max. pressure 14bar
Max. clamping force/roller 100daN
Max. roller rim speed 800m/min
Centering precision (precision tolerance to DIN ISO1101) on the complete clamping area of the same clamping conditions 0,02mm
Repeatability with steady-rest aligned on the clamping diameter 0,005mm.

ATTENZIONE :
APERTURA A MOLLA
CHIUSURA CON LIQUIDO REFRIGERANTE
il liquido refrigerante deve essere filtrato
min. 0,03 - max. 0,05

ATTENZIONE :
OPENING THROUGH SPRING SYSTEM
CLOSING THROUGH COOLANT SYSTEM
The Coolant must be filtered min. 0,03 - max. 0,05

DATE/DATE: 12/02/2024

05308600-R011

Subject to technical changes