


05411400 - LUNETTA D55 L-R D6-70 SLU-X-1M H70

Type	STEADY REST Self-centering steady rest for turret
Mounting	CYLINDRICAL SHANK 55
Tool output	Gripping jaws Ø6-Ø70
Coolant	N.A.
H [mm]	70
Ø Min [mm]	6
Ø Max [mm]	70
Max pressure [bar]	18
Accessories	N.A.
Notes	N.A.
Mounting tips	Lower turret



Always check live tool dimensions on the turret

Druckfeder D-313G
 Federhöhe 6,651 N/mm
 max. Federkraft 392 N
 Federkraft bei "Linette geschlossen" 389 N
 Federkraft bei "Linette geöffnet" 190,4 N

Druckfeder D-313W
 Federhöhe 5,961 N/mm
 max. Federkraft 377,4 N
 Federkraft bei "Linette geschlossen" 342,7 N
 Federkraft bei "Linette geöffnet" 137,1 N

ATTENZIONE :
 APERTURA A MOLLA
 CHIUSURA CON LIQUIDO REFRIGERANTE
 il liquido refrigerante deve essere filtrato
 min. 0,03 - max. 0,05

ATTENZIONE :
 OPENING THROUGH SPRING SYSTEM
 CLOSING THROUGH COOLANT SYSTEM
 The Coolant must be filtered min. 0,03 -
 max. 0,05

DATE/GATA
 12/02/2024 **05411400-R011**

Subject to technical changes