


# 05411400 - LUNETTA D55 L-R D6-70 SLU-X-1M H70

Type	STEADY REST Self-centering steady rest for turret
Mounting	CYLINDRICAL SHANK 55
Tool output	Gripping jaws Ø6-Ø70
Coolant	N.A.
H [mm]	70
Ø Min [mm]	6
Ø Max [mm]	70
Max pressure [bar]	18
Accessories	N.A.
Notes	N.A.
Mounting tips	Lower turret



Always check live tool dimensions on the turret

**Druckfeder D-313G**  
 Federhöhe 6,651 N/mm  
 max. Federkraft 392 N  
 Federkraft bei "Linette geschlossen" 389 N  
 Federkraft bei "Linette geöffnet" 190,4 N

**Druckfeder D-313W**  
 Federhöhe 5,961 N/mm  
 max. Federkraft 377,4 N  
 Federkraft bei "Linette geschlossen" 342,7 N  
 Federkraft bei "Linette geöffnet" 137,1 N

**ATTENZIONE :**  
 APERTURA A MOLLA  
 CHIUSURA CON LIQUIDO REFRIGERANTE  
 il liquido refrigerante deve essere filtrato  
 min. 0,03 - max. 0,05

**ATTENZIONE :**  
 OPENING THROUGH SPRING SYSTEM  
 CLOSING THROUGH COOLANT SYSTEM  
 The Coolant must be filtered min. 0,03 -  
 max. 0,05

**Subject to technical changes**

DATE/GATA	12/02/2024
	05411400-R011